



**MATERIAL:** CONSTRUCTED FROM AN EXTRUDED POLYSTYRENE BASE, A FLEXIBLE CEMENTITIOUS BASECOAT AND A REVOLUTIONARY, SMOOTH POLYMER MODIFIED PLASTER FINISH.

**NOTES:** THE LOOK AND FEEL OF A SEAMLESS PLASTER COVE. FABRICATED IN 8' LENGTHS, CUT AND MITRED TO FIT, THEN PRIMED AND PAINTED IN THE FIELD.

LUMAROC MOUNTS TO THE WALL USING SHEET ROCK SCREWS AND A GYPSUM BASED DRYWALL COMPOUND TO THE BACK AND TO THE JOINTS.

LIGHTING FIXTURES SHOULD BE MOUNTED TO THE WALL INDEPENDENT OF THE COVE FITTING.

LIGHT WEIGHT DESIGN.  
LUMAROC IS A STABLE LUMINAIRE FITTING THAT WILL NOT CRACK SHRINK OR SWELL.

## LUMAROC TRAY COVE CAT # LRTC-5500-5750

SCALE:  
NONE

DATE:  
11/31/2010

DRAWN BY:  
MJW

SHEET:  
1 of 1

## CLASSIC COVES

PO BOX 266 GARWOOD, NJ 07027  
PHONE: 908-344-1776 Fax: 908-345-6176  
[www.classiccoves.com](http://www.classiccoves.com)

FIRE RATED - ASTME-84